

Installation process

SETUP PROGRAM

Mountain bike



1 Pre-installation preparation

Visible Professional Quality • We are dedicated to serving you.

01 >>next----- 02 >>next----- 03 >>next----- 04 >>next-----



Pre-installation preparation



Take out the bicycle



Cut off the fixed zip ties



Remove the packaging protective pieces and discard them

2 Install the handlebars

Visible Professional Quality • We are dedicated to serving you.

01 >>next----- 02 >>next----- 03 >>next----- 04 >>next----- 05 >>next----- 06 >>next-----



Loosen the handlebar stem screws



Adjust the handlebar stem to the correct angle by 180 degrees



Adjust the stem and front fork to the correct orientation



Loosen the front stem screws of the stem



Correctly install the handlebar at the proper angle.



Cross-tighten the fixing screws, and tighten them in sequence.

3 Install the front wheel

Non-quick-release

● 01 >>next ● 02 >>next ● 03 >>next ● 04 >>next ● 05 >>next



Remove the front fork protective cover and discard it

Loosen the outermost screws on both sides of the front wheel

Front wheel placed in the middle of the front fork and ensure that the brakes are on the left side of the bike

Install the front wheel anti-loosening pad

Tighten the front wheel screws

4 Install the saddle

● 01 >>next ● 02 >>next ● 03 >>next



Loosen the quick-release

Insert the seatpost into the seat tube. Tighten the screws

Adjust the saddle to the appropriate height and tighten the quick-release

5 Install reflectors

● 01 >>next ● 02 >>next ● 03 >>next



Installation of front and rear reflectors

Positioning of rear reflector

Positioning of front reflector

6 Install mudguards

● 01 >>next ● 02 >>next ● 03 >>next



Fix the front mudguard screws to the small holes in the middle of the front fork

Loosen the quick-release, then insert the rear mudguard into the quick-release, tighten, and fasten

After installation and adjustment

7 Install pedals

● 01 >>next ● 02 >>next ● 03 >>next



Pedal letters ("R" for right, "L" for left)

Tighten the right pedal clockwise

Tighten the left pedal counterclockwise

Please ensure tightening to prevent stripping

8 Brake adjustment

● 01 >>next ● 02 >>next ● 03 >>next ● 04 >>next ● 05 >>next



Visually inspect wheel rotation for any contact with brake pads

Tighten the two screws above and below the brake caliper

Move the brake caliper to visually ensure the brake pads are in the middle of the brake pads and tighten the adjustment screws

1. Loosen the brake cable core compression screw
2. Adjust the brake clearance by tightening or loosening the brake cable core

9 Install the rack

● 01 >>next ● 02 >>next ● 03 >>next



First install the rear rack supports

The installation of the front support bar of

Then install the rack column to the rear rack

Installation complete

10 Install flashlight holder

● 01 >>next ● 02 >>next



Flashlight holder installs on the handlebar

Insert flashlight into the holder slot