


# Volant King Table Tennis Table Installation Instruction

#### Preface

Thank you for purchasing Double Fish products; this instruction is for model Volant King, T.T. tables. If this is your first time to assemble or use such products, please make sure the instruction is carefully read, which would be helpful for installation.

## (Description & Quantity of each part for assembling)

The picture of each part for disperse





Number	Name and Size	数量 Quantity
1	Table top	2 *
2	Leg supporter	2
3	B Fixable screw bolt B	8
4	Table leg	2
5	A Fixable screw bolt A	8
6	Connection bridge	1
7	Connection shaft	1
8	Screw bolt: M8 X 25	4
9	Tool key for special assembling	2
10	Table tennis net assembly	1 套


\*Notation: A,B two part 8

# (Assembly methods)

Step 1: According to picture 1. Opening the packing and take out the N0.6 connection bridge.













Step 5: According to picture 5. Use the same method to connect the other table leg and the connection bridge.


picture 5














Step 10: According to picture 10. When finish installing the table.please put the undercarriage of the connection bridge to the original position.







\* Finish all the above steps to have the table assembled. Hope you can enjoy table tennis sports.




### Demolishing scheme







Step 2: dismantle ball countertops and shelves connected on the 5th of tight bolts A. The table to move from the lower frame and the ball . as shown in Figure 2




Step 3: remove the lock on the 8th member M10 X 25 bolts, then7 and then remove the cassette connected connecting the fork assembly ,as shown in Figure 3




Step 4: Remove the No. 3 adapter bolt B to connect the pieces of the 2nd legs of the table as shown in Figure 4



Step 5: According to picture 5
Open the lock bolt of the
undercarriage.spin 90 degree to the
concaved hole and then lock it.



Step 6: adapter removed with the 5th the bolts A connecting 4 pieces of legs of the table and the 6th member the connection bridge, shown in Figure 6



Completed the above steps , the table tennis table can be dismantled completed the good dismantle down the accessories please clean up for the next installation .